

MT100 Specs & Compare

MT100 Key Specifications	
Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi

Auxiliary Std Flow	12 gal/min
Width	35.6 in
Height to Bucket Hinge Pin	80.9 in

Engine	
Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	55 in³
Number of Cylinders	3
Horsepower	24.8 hp

Performance	
Rated Operating Capacity (ISO)	1,000 lb
Carry Position ROC with Standard Counterweight -UnderCarriage Position	1,300 lb
Tipping Load	2898 lb
Operating Weight	3390 lb
Ground Pressure (Rubber)	5.25 psi
Travel Speed	4.1 mph
Travel Speed - Reverse	2.9 mph

Capacities	
Fuel Tank	7 gal

Hydraulic System	
Pump Capacity	12 gal/min
System Relief @ Quick Couplers	2,900 psi
Auxiliary Std Flow	12 gal/min

Dimension	
Length	106.2 in
Width	35.6 in
Height	54.6 in
Height to Bucket Hinge Pin	80.9 in
Length of track on ground	41.4 in
Reach @ Maximum Height	18.6 in

Features	
Lift-Arm Support	Standard
Auxiliary Hydraulics	Standard
Spark Arrestor Muffler	Standard
Bob-Tach Attachment System	Standard
Reverse Travel Stop Panel	Not Applicable
Wide Track	Optional
Neutral Start Interlocks	Standard
Lift Arm Lockout With Manual Bypass	Standard
Tilt Lockout	Standard
Built-In Tie Down & Crane/Lift Locations	Standard
Ride-on Platform	Standard