

T190 Specifications

	T190 Compact Track Loader (2004)	T190 Compact Track Loader	T190 Compact Track Loader (2008)
T190 Key Specifications			
Rated Operating Capacity (ISO)	1,900 lb	1,900 lb	1,900 lb
Operating Weight	7244 lb	7775 lb	7612 lb
Ground Pressure (Rubber)		5.03 psi	4.9 psi
Auxiliary High Flow	26.4 gal/min	26.4 gal/min	25.5 gal/min
Auxiliary Std Flow		16.9 gal/min	16.3 gal/min
Joystick Control	Not Applicable	Optional	Optional
Engine			
Engine Cooling	Liquid	Liquid	Liquid
Engine Fuel	Diesel	Diesel	Diesel
Horsepower	56 hp	66 hp	66 hp
Turbocharged Engine	yes	yes	yes
Emissions Tier (EPA)		Interim Tier 4	Tier 2

Performance				
Rated Operating Capacity (ISO)	1,900 lb	1,900 lb	1,900 lb	
Operating Capacity (50% of Tip)	2715 lb	3642 lb	3426 lb	
Tipping Load	5430 lb	7283 lb	6851 lb	
Operating Weight	7244 lb	7775 lb	7612 lb	
Travel Speed	7 mph	7.3 mph	7.1 mph	
Ground Pressure (Rubber)		5.03 psi	4.9 psi	

Capacities				
Fuel Tank	26.8 gal	28 gal	28 gal	

Hydraulic System				
System Relief @ Quick Couplers	3,300 psi	3,250 psi	3,250 psi	
Auxiliary High Flow	26.4 gal/min	26.4 gal/min	25.5 gal/min	
Auxiliary Std Flow		16.9 gal/min	16.3 gal/min	

Dimension				
Length	101.8 in	101.9 in	101.8 in	
Length without Attachment	101.8 in	101.9 in	101.8 in	
Length with Standard Bucket	130.3 in	130.3 in	130.3 in	
Width	66 in	66 in	66 in	
Width (with bucket)	68 in	68 in	68 in	
Height	76.3 in	76.3 in	76.3 in	
Height with Operator Cab	76.3 in	76.3 in	76.3 in	
Height to Bucket Hinge Pin	118.2 in	118.2 in	118.2 in	
Reach @ Maximum Height	29.6 in	30.9 in	30.9 in	
Turning Radius	78.8 in	78.8 in	78.8 in	

Length of track on ground	55.2 in	55.2 in	55.2 in
Track Width	12.6 in	12.6 in	12.6 in
Track Width - Optional		15.8 in	16 in

Features				▲
Joystick Control	Not Applicable	Optional	Optional	
Air Conditioning	Optional	Optional	Optional	
BICS System (Interlock)	Standard	Standard	Standard	
Cab Heater	Optional	Optional	Optional	
Operating Lights	Standard	Standard	Standard	
Suspension Seat	Standard	Standard	Standard	
Two Speed Travel	Not Applicable	Not Applicable	Not Applicable	
Deluxe Instrumentation	Optional	Optional	Optional	
Hydraulic Bucket Positioning	Optional	Optional	Optional	
Auxiliary Hydraulics	Standard	Standard	Standard	
Bob-Tach Attachment System	Standard	Standard	Standard	
Cab Enclosure	Optional	Optional	Optional	
Sound Option	Optional	Optional	Optional	
Rear Window	Standard	Standard	Standard	
Seat Belt	Standard	Standard	Standard	
Spark Arrestor Muffler	Turbo charger	Standard	Standard	
Lift-Arm Support	Standard	Standard	Standard	
Spark Arrestor	AVAIL-STD	Turbo	Turbo	
Backup Alarm		Standard		
Engine Shutdown		Standard	Standard	
High Flow Option		Optional	Optional	
Power Bob-Tach		Optional	Optional	

ACS (Switchable
Controls)

Optional

Ride Control

Optional

Optional

Horn

Standard

Adjustable Seat

Standard

Power Qtach

Optional

Optional