

TECHNICAL DATA

Working direction	Floor, Wall
Tool chuck type	TE-S
Weight according EPTA-Procedure 01/2003	27.6 lb.
Single impact energy	19.2 ft-lbf
Full hammering frequency	1950 impacts/minute
Max. chiseling performance	476 in ³ /min
Dimensions (LxWxH)	28 x 5.6 x 12 in
Triaxial vibration for chiseling into concrete	5.9 m/s ² ¹
A-weighted emission sound pressure level	85 dB (A) ²
Dust removal system available	TE DRS-B

FEATURES & APPLICATIONS

Features

- High versatility – in-line design for floor breaking and ergonomic side handle for occasional wall breaking
- Maintenance-free brushless SR motor and triple-chamber lubrication systems for longer service intervals and tool lifetime
- Exceptionally low tool vibration due to Hilti AVR sub-chassis (Active Vibration Reduction) system
- Detachable supply cord for fast and easy replacement of damaged/broken supply cords on the jobsite
- Optional TE DRS-B dust removal system, which collects up to 95% of dust

Applications

- Demolishing concrete and masonry at floor level or below waist level
- Renovating floors of all kinds
- Removing tiles, bushing and compacting
- Corrective chiseling, such as adjustments to door and window openings