

Combihammer TE 40-AVR

Sense the power feel the comfort



Applications

- Hammer drilling in concrete, masonry and natural stone (recommended diameter range: 14 to 24 mm)
- Light chiselling work on concrete and masonry
- Socket cutting using percussion core bits up to 90 mm dia
- Drilling with high torque in wood and metal

Advantages

- The most powerful combihammer in the TE-C class (SDS-plus)
- Maximum working comfort thanks to innovative, perfectly balanced design with ergonomic D-grip
- Extremely wide range of applications thanks to rapidly interchangeable chucks: TE-C Click chuck (SDS-plus), 3-jaw key chuck and keyless quick-release chuck
- Active vibration Reduction (AVR) for lower vibration, less tiring to use and higher daily productivity

Technical data

TE 40-AVR	
Power range	1010 W
Single impact energy as per EPTA 05/2009 (100% joules)	4.9 J
Speed 1 (no load)	550 rpm
Hammering speed (under load 100%)	3180 impacts/minute
Dimensions (LxWxH)	425 x 113 x 243 mm
Weight in accordance with EPTA-Procedure 01/2003	5.6 kg
Drilling Performance	60 cm³/min @ Ø 12 mm 86 cm³/min @ Ø 16 mm 80 cm³/min @ Ø 20 mm